

Swintec<sup>®</sup>

# The 2640 Electronic Display Typewriter

A smart collection of characters.



# SWINTEC MODEL 2640 ELECTRONIC DISPLAY TYPEWRITER SPECIFICATIONS

<b>Sculptured Keyboard</b>	For ease of typing
<b>Removable Platen</b>	For easy cleaning
<b>Adjustable, 40 Character Liquid Crystal Display (LCD)</b>	For visual typing and mode/function indication
<b>Memory Capacity</b>	112,000 characters
<b>Memory Protection</b>	Retains margins, tabs and stored files for 5 years
<b>Number of Characters</b>	100 including Keyboard II characters
<b>Number of Print Keys</b>	46
<b>Paper Capacity/Writing Line</b>	15" / 11.5"
<b>Print Speed</b>	20 CPS
<b>Correction Memory</b>	700 characters within 10 lines
<b>Key Buffer</b>	For quick spurts of typing
<b>Pitch Selector and Margin Scale</b>	10, 12, 15 and PS (Proportional Spacing)
<b>Line Spacing Selector</b>	1, 1.5 and 2
<b>Impression Control</b>	Light, Medium and Heavy
<b>Copy Capacity</b>	1 original + 4 copies
<b>Tab Set / Clear Key</b>	Programmable at 30 positions
<b>Express Key</b>	Returns carriage to the left margin without line feed
<b>Programmable Hot Zone</b>	Allows user to control the look of the right margin
<b>Relocation Key</b>	Returns carriage to last typed position after editing or correction
<b>Programmable Line Spacing</b>	For unique line spacing applications
<b>Half Space Key</b>	For special spacing and insertion of characters
<b>Index/Reverse Index</b>	Rotates platen up/down in 1/2 line increments
<b>Independent Repeat Key</b>	For repeat action of all keys
<b>Deep Depress Repeat Action Keys</b>	Space Bar, Correction Key, Backspace Key, Index/Reverse Index Keys
<b>Shift Lock Key Indicator</b>	Light Emitting Diode
<b>Print Key</b>	Provides quick access to print a file
	<b>Code Functions:</b>
<b>Alpha Lock</b>	Enables numbers and upper case letters to be typed without shifting
<b>Automatic Centering</b>	Centers a line of text between margin settings, between tabs, or at any desired position
<b>Automatic Return</b>	Returns carriage if space or hyphen is typed in the hot zone. Wordwrap system in LP, Just and Store Modes
<b>Automatic Underlining</b>	Word by word and continuous
<b>Automatic Vertical Line</b>	Draws vertical lines for graphs and charts
<b>Backspace 1/120"</b>	For fine incremental spacing and PS
<b>Back Tab</b>	Line feeds and returns carrier to the last tab position where text was typed for quick column entry
<b>Bold Print</b>	For added emphasis of typed words
<b>Center Tab</b>	Center characters typed at tab setting

<b>Column Layout</b>	Automatic format for creating columns
<b>Decimal Tab</b>	Automatically aligns numbers by their decimal points
<b>Flush Right Tab</b>	Aligns last character typed with tab setting
<b>Keyboard II</b>	Provides access to additional characters for special typing needs
<b>Micro Up/Down</b>	Rotates platen up/down in 1/96" increments
<b>Overlay</b>	Allows two characters to be typed at the same position [Ø]
<b>Paper Eject</b>	Automatically ejects the paper
<b>Paragraph Indent</b>	Creates a temporary left margin
<b>Required Hyphen / Space</b>	Prevents the division of two words or hyphenated words at the end of a line
<b>Right Margin Flush</b>	Aligns text with the right margin
<b>Top Margin Setting</b>	Programmable, for variable top margin setting
<b>Word Delete</b>	Automatically deletes an entire word
<b>Mode Key</b>	Provides quick access to four different typing modes
<b>Normal Print</b>	Prints directly to the paper
<b>Line Print</b>	Prints one line at a time
<b>Justified Print</b>	Prints text with an even right margin
<b>Store Mode</b>	Accesses memory functions
<b>Memory Functions: Memory Size</b>	112,000 characters stored in 1 to 100 files
	<b>Memory Types:</b>
<b>Text Files</b>	For storage of text with margins and tabs
<b>Phrase Files</b>	For storage of text only, no margins and tabs
<b>Format Files</b>	For storage of margins and tabs only
<b>Variable Files</b>	For storage of formats for pre-printed forms
<b>Bidirectional Global or Manual Search and Replace</b>	For quick search and/or replace of words or phrases in either direction from any point in the text (with global, manual, yes/no selections)
<b>Block / Move / Copy / Delete / Print</b>	Provides the capability to move, copy, delete or print a specified block of text in a stored file

<b>Capacity Code</b>	Displays remaining storage memory
<b>Chain Recall</b>	Provides the capacity to select and continuously print 2 to 40 stored files
<b>Column Counter</b>	Indicates current position on the line
<b>Combine Phrase and Text Files</b>	Allows a phrase file to be stored in a text file and recalled at time of print
<b>Copy File</b>	Allows stored files to be copied
<b>Emergency Stop</b>	Touching the space bar stops printing in print mode
<b>File Delete</b>	For reuse of memory space
<b>File Listing</b>	Prints or displays the name, type and a preview of each store file
<b>Page Length Selector</b>	Allows the page length to be specified
<b>Pause Command</b>	Temporarily stops printing during file recall
<b>Stop Code</b>	Interrupts printing temporarily for variable text insertion
<b>Text Editing</b>	Overstrike, Insert, Delete
<b>Paper Injection</b>	Automatically inserts paper
<b>Paper Stand</b>	With adjustable paper guide and page end indicator
<b>Platen Knob</b>	Located on the left side, to manually rotate platen roller
<b>Sound and Glare Shield</b>	For quiet, easily readable typing
<b>Dust Cover</b>	Form fitted
<b>Power</b>	115V AC @ 60 HZ
<b>UL Approval</b>	Standard No. 114
<b>Dimensions</b>	H5.2" (132mm), W-18.9" (480mm), D-16" (406mm)
	<b>Supplies:</b>
<b>Drop-in Printwheels</b>	Over 50 types available in various pitches, styles and languages including scientific
<b>Cartridge Ribbons</b>	Correctable Carbon, Multistrike and Fabric
	<b>Options:</b>
<b>SPELLPROOF</b>	80,000 word main dictionary, plus a 300 word, user-created, custom dictionary

**Swintec** CORPORATION 320 W. Commercial Avenue  
P.O. Box 356, Moonachie, NJ 07074

Specifications subject to change without notice.  
SPELLPROOF is a registered trademark of Swintec Corporation.  
Date of print 6/93. Printed in U.S.A. © 1993 Swintec Corporation.

VO19306

SW®

Reorder #ADV-2640-BRO