

Swintec®

THE SWINTEC 7040

One look tells you it's different.
One touch shows you.



SWINTEC MODEL 7040 ELECTRONIC TYPEWRITER

SPECIFICATIONS

Sculptured Keyboard	For ease of typing	Bold Print	For added emphasis of typed words	Capacity Code	Displays remaining storage memory
Removable Platen	For easy cleaning	Center Tab	Centers characters typed at tab setting	Chain Recall	Provides the capability to select and continuously print 2 to 40 stored files
Adjustable, 40 Character Liquid Crystal Display (LCD)	For visual typing and mode/function indication	Column Layout	Automatic format for creating columns	Column Counter	Indicates current position on the line
Memory Capacity	48,000 characters	Decimal Tab	Automatically aligns numbers by their decimal points	Combine Phrase and Text Files	Allows a phrase file to be stored in a text file and recalled at time of print
Memory Protection	Retains margins, tabs, and stored files for 5 years	Flush Right Tab	Aligns last character typed with tab setting	Copy File	Allows stored files to be copied
Number of Characters	100 including Keyboard II characters	Keyboard II	Provides access to additional characters for special typing needs	Emergency Stop	Touching the Space Bar stops printing in print mode
Number of Print Keys	46	Micro up/down	Rotates platen up/down in 1/64" increments	File Delete	For reuse of memory space
Paper Capacity/Writing Line	17" x 13.5"	Overlay	Allows two characters to be typed at the same position (Ø)	File Listing	Prints or displays the type and first 40 characters of each stored file
Print Speed	22 CPS	Paper Eject	Automatically ejects the paper	Page Length Selector	Allows page length to be specified. Display prompt indicates number of lines remaining on page
Correction Memory	500 characters within a full page	Paragraph Indent	Creates a temporary left margin	Pause Code Stop Code	Temporarily stops printing. Stops print temporarily for variable text insertion
Key Buffer	For quick spurts of typing	Required Space/Hyphen	Prevents division of two words or hyphenated words at the end of a line	Text Editing Paper Injector	Overstrike, Insert, Delete. Automatically inserts paper
N-Key Roll Over System	Enables multiple keys to be depressed and printed in the exact order struck	Right Margin Flush	Aligns text with the right margin	Paper Stand	With adjustable paper guide and page end indicator
Pitch Selector and Margin Scale	10, 12, 15, and PS (Proportional Spacing)	Top of Form Setting	For variable top margin setting	Platen Knob	Located on left side, to manually rotate platen roller
Power On Indicator	Light Emitting Diode	Word Delete	Deletes entire word with one operation	Sound and Glare Shield	For quiet, easily readable typing
Line Spacing Selector	1, 1.5, 2, 3, and variable spacing manually	Mode Key:	Provides quick access to four different typing modes	Dust cover Power	Form fitted 115V AC @ 60 HZ, 60 Watts
Impression Control	Light, Medium, Heavy	Normal Print	Prints directly to the paper	UL Approval Dimensions	Standard No. 114 H-7"(177mm), W-21"(533mm), D-19"(482mm)
Copy Control Lever	Adjusts distance between carrier and platen	Line Print	Prints one line at a time	Supplies:	
Copy Capacity	1 original + 7 copies via copy control lever	Justified Print	Prints text with an even right margin	Drop-in Cassette Printwheels	Over 50 styles available in various pitches, styles and languages including scientific
Tab Set/Clear Key	Programmable at 30 positions	Store Mode	Accesses memory functions	Cartridge Ribbons	High-Yield Correctable Carbon
Alpha Lock Key	Enables numbers and upper case letters to be typed without shifting	Memory Functions:		Options:	
Express Key	Returns carriage without line feed	Memory Size	48,000 characters stored in 1 to 100 files	SPELLPROOF	80,000 word main dictionary, plus a 300 word, custom-created, user dictionary
Relocation Key	Returns carriage to last typed position after editing or correction	Memory Types:			
Half Space Key	For special spacing and insertion of characters	Text Files	For storage of text with margins and tabs		
Index/Reverse Index	Rotates platen up/down in 1/2 line increments	Phrase Files	For storage of text only, no margins and tabs		
Independent Repeat Key	For repeat action of all keys	Format Files	For storage of margins and tabs only		
Deep Depress Repeat Action Keys	Space Bar, Correction Key, Back Space Key, Index/Reverse Index Keys	Variable Files	For storage of formats for pre-printed forms		
Shift Lock Key Indicator	Light Emitting Diode	Bidirectional Global or Manual Search and Replace	For quick Search and/or Replace of words or phrases in either direction from any point in the text. (With Global, Manual, Yes/No selections)		
Print Key	Quick access to print a file	Block Move/Copy/Delete/Print	Provides the capability to move, copy, delete or print a specified block of text in a stored file		
Code Functions:					
Automatic Centering	Centers line of text between margin settings, between tabs, or at any desired position				
Automatic Return	Returns carriage if space bar or hyphen is typed in the hot zone. Word wrap system in LP and JUST Modes				
Automatic Underlining	Word by word and continuous				
Automatic Vertical Line	Draws vertical lines for graphs and charts				
Backspace 1/20"	For fine incremental spacing and PS				
Back Tab	For quick column entry—line feeds and returns carrier to tab setting at left				

Swintec
CORPORATION

320 West Commercial Avenue
P.O. Box 356, Moonachie, NJ 07074

Specifications subject to change without notice.
SPELLPROOF is a registered trademark of Swintec Corporation.
Printed in U.S.A. © 1989 Swintec Corporation

V058902

Reorder #: ADV-7040-BRO